



150 Aqua Trap®

True to its name, this patented perimeter "Agua Dam" forms a tray that can hold up to 6 litres of water per square meter.

The textile top surface is high pressure moulded into a bubble design on an indestructible rubber base to withstand the heaviest of foot traffic.

Unsurpassed ability to scrape debris from shoes while maintaining its great looking appearance for the longest time. Unique slip resistant gripper pattern on the back.

Recommended use:

- Heavy traffic
- For placement inside entrances of hotels, shops, department stores, schools, universities, restaurants, supermarkets.

Specifications:

- · Polyester fibres
- Backing: Natural rubber
- Fabric covered borders: 2.5 cm on all sides
- Overall thickness: 13 mm
- Weight: 5,2 kg/m²
- Fire rating: ASTM D2859 passes DOC-FF-1-70

Standard sizes:

- 60cm x 90cm
- 90cm x 150cm
- 120cm x 180cm

• Brown, Blue, Charcoal, Grey, Red Black

Cleaning instructions:

• Vacuum/shampooing or use injection/extraction method to clean















PRODUCT TESTING











Brown (BR)

Blue (BU)

Charcoal (CH)

Grey (GY)



Red (RB)

150 Aqua Trap®

Art. nr.	Dimensions	Weight kg
150S0023	60cm x 90cm	2,5
150S0035	90cm x 150cm	6,1
150S0046	120cm x 180cm	9

Colours: Brown (BR), Blue (BU) Charcoal (CH), Grey (GY), Red (RB)

150 Aqua Trap®

GENERAL DESCRIPTION

Туре	Indoor Absorbant - Loose Lay Carpet Mats	
Description	Absorbent carpet mat	
Recommended use	Indoor	
Category	Dust Control Matting Heavy traffic	
Colours	Brown, Blue, Charcoal, Grey, Red Black	
Special remarks	Patented raised perimeter « Aqua Dam »	
Edges	Fabric covered borders: 2.5 cm on all sides	

TECHNICAL SPECIFICATIONS

Material	Polyester fibres
Backing	Natural rubber
Process	Needle punch
Yarn Construction	Needle punched
Pile weight	850 g/m²
Total weight	5,2 kg/m ²
Overall thickness	13 mm

TESTS

Absorption capacity	TNO W6034	3.6 l/m²	
Fire rating	EN 13501	ASTM D2859 passes DOC-FF-1-70	
Sustainability	Recyclable material, Contributes to a cleaner environment by reducing need of cleaning chemicals		
Surface flammability	ASTM D2859	Pass	

DIMENSIONS

Standard sizes	Full rolls	Custom lengths
60cm x 90cm		
90cm x 150cm		
120cm x 180cm		

