



Indoor - Medium traffic

199 Logo Imperial™

The Logo Imperial™ high quality multifunctional dust control mat is densely tufted with an open Frieze tuft for true depth of colour and a trackless surface to ensure a high water absorption capacity and dirt removal for a highly effective solution. A durable vinyl backing with a smooth finish adapts to any surface.

Logo Imperial™ can be fully customized with BrilliantStep™ state-of-the-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.

Artwork is supplied within 24-hours. The mat is printed 24 hours after the artwork approval is given.

Recommended use:

- · Medium traffic
- For loose lay placement

Specifications:

- 100% polyamide 6.6 yarns
- Backing: Black vinyl (DOP free)
- Vinyl borders: 2.5 cm on all sides
- Overall thickness: 8 mm
- Weight: 3 kg/m²
- Fire rating EU: Bfl-S1
- Special characteristics: Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of

Recommended accessories:

083 Bevelled Nosing 2 mm

Standard sizes:

- 60 cm x 90 cm
- 90 cm x 120 cm
- 90 cm x 150 cm
- 120 cm x 180 cm
- 120 cm x 240 cm

Custom lengths:

- 135 cm x linm
- 150 cm x linm
- 200 cm x linm

Colours:

• Unlimited colour possibilities

Cleaning instructions:

· Vacuum clean

PRODUCT TESTING

























199 Logo Imperial™

Art. nr.	Dimensions	Weight kg
199S0023WH	60 cm x 90 cm	1,5
199S0034WH	90 cm x 120 cm	2,9
199S0035WH	90 cm x 150 cm	3,4
199S0046WH	120 cm x 180 cm	5,5
199S0048WH	120 cm x 240 cm	10,1
199C0051WH	135 cm x linm	3,4
199C0060WH	150 cm x linm	4,5
199C0078WH	200 cm x linm	6



199 Logo Imperial™

GENERAL DESCRIPTION

Designation	Logo Matting	
Туре	Indoor Absorbant - Printed Logo Mats	
Description	199 Logo Imperial™ can be fully customized with BrilliantStep™ state-of-the-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individu-	
	al image.	
Surface	Smooth even surface	
Category	Logo Matting	
Recommended use	Indoor Medium traffic	
Colours	Unlimited colour possibilities	
Edges	Vinyl borders: 2.5 cm on all sides	

TECHNICAL SPECIFICATIONS

Material	100% polyamide 6.6 yarns
Backing	Black vinyl (DOP free)
Primary backing	Nonwoven PET/PA
Process	Tufting
Yarn Construction	Cut loop pile - frieze
Pile weight	700 g/m ²
Total weight	3 kg/m²
Pile height	0,66 mm
Overall thickness	8 mm

TESTS

Absorption capacity	TNO W6034	4 l/m²	
Fire rating EU	EN 13501	Bfl-S1	
Static charge	ISO 6356	<0.1	
Comfort class	EN 1307	LC3	
Light Fastness	ISO 105 B02	5	
Water fastness	ISO 105 B01	4	
Rubbing fastness	ISO 105 X12	4	
Salt water	ISO 105 E02	4	
Shampoo	BS 1006	4	
Organic solvents	ISO 105 X05	4	
Sustainability	Recyclable material, Contributes to a cleaner environment by reducing need of cleaning chemicals		
Surface flammability	ASTM D2859	Pass	

DIMENSIONS

Standard sizes	Full rolls	Custom lengths
60 cm x 90 cm		135 cm x linm
90 cm x 120 cm		150 cm x linm
90 cm x 150 cm		200 cm x linm
120 cm x 180 cm		
120 cm x 240 cm		

