



Justrite Safety Group

Indoor Absorbant - Printed Logo Mats

193 Logo Standard™



Indoor - Light traffic

193 Logo Standard™

Logo Standard™ can be fully customized with BrilliantStep™ state-of-the-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.

Logo Standard™ is the ideal promotional matting solution for light duty applications. Using BrilliantStep™ full colour printing with almost infinite colour combinations, the densely tufted entrance mat allows fine printing and true colour presentation.

A durable vinyl backing with smooth finish adapts to any surface. The BrilliantStep™ printing method ensures brilliant colours all the way through with a colour fastness that is ensured, in accordance with DIN54006. Artwork supplied in 24-hours. Mat is printed 24 hours after artwork approval is given!

Recommended use:

- Light traffic
- For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, specialty stores.

Specifications:

- Velours 100% polyamide 6.6 high twist yarns
- Backing: Black vinyl (DOP free)
- Vinyl borders: 2.5 cm on all sides
- Overall thickness: 6 mm
- Weight: 2,7 kg/m²
-

Recommended accessories:

- 083 Bevelled Nosing 2 mm

Standard sizes:

- 60cm x 90cm; 90cm x 120cm; 90cm x 150cm; 90cm x 300cm; 120cm x 180cm

Custom lengths:

- 90cm x linm; 120cm x linm

Colours:

- White

Cleaning instructions:

- Vacuum clean



PRODUCT TESTING



193 Logo Standard™

Art. nr.	Dimensions	Weight kg
193S0023WH	60cm x 90cm	1,5
193S0034WH	90cm x 120cm	3,4
193S0035WH	90cm x 150cm	4,9
193S0046WH	120cm x 180cm	6
193S0310WH	90cm x 300cm	7,5
193C0036WH	90cm x linm	3
193C0048WH	120cm x linm	3,9



193 Logo Standard™

GENERAL DESCRIPTION

Type	Indoor Absorbant - Printed Logo Mats
Description	Affordable absorbent carpet mat with printed custom logo or design.
Recommended use	Indoor
Surface	Custom logo or design
Category	Logo Matting Light traffic
Colours	White
Edges	Vinyl borders: 2.5 cm on all sides

TECHNICAL SPECIFICATIONS

Material	Velours 100% polyamide 6.6 high twist yarns
Backing	Black vinyl (DOP free)
Primary backing	Nonwoven PET/PA
Process	Tufting
Yarn Construction	Cut loop pile - velours
Pile weight	405 g/m ²
Total weight	2,7 kg/m ²
Pile height	0,6 mm
Overall thickness	6 mm

TESTS

Absorption capacity	TNO W6034	3 l/m ²
Static charge	ISO 6356	<0.1
Comfort class	EN 1307	LC3
Light Fastness	ISO 105 B02	5
Water fastness	ISO 105 B01	4
Rubbing fastness	ISO 105 X12	4
Salt water	ISO 105 E02	4
Shampoo	BS 1006	4
Organic solvents	ISO 105 X05	4
Sustainability	Recyclable material, Contributes to a cleaner environment by reducing need of cleaning chemicals	
Surface flammability	ASTM D2859	Pass

DIMENSIONS

Standard sizes	Full rolls	Custom lengths
60cm x 90cm		90cm x linm
90cm x 120cm		120cm x linm
90cm x 150cm		
90cm x 300cm		
120cm x 180cm		