## TouchNTuff® 92-600 92-605

NBR NITRILE			SPLASH			CHEMICAL & LIQUID PROTECTION			
STYLE #	LINER MATERIAL	CUFF STYLE	COLOUR	GRIP DESIGN	THICKNESS MM	POW- DER- FREE	EN SIZE	LENGTH MM	PACKAGING
92-600	Not applicable	Rolled Beaded	Green	Smooth	0.12	Yes	6½-7, 7½-8, 8½-9, 9½-10	240	100 gloves in a box, 10 boxes in a carton
92-605	Not applicable	Rolled Beaded	Green	Smooth	0.12	Yes	6½-7, 7½-8, 8½-9, 9½-10, 10½-11	300	100 gloves in a box, 10 boxes in a carton





**Proven splash** resistance against hazardous chemicals

PRIMARY INDUSTRIES



**IDEAL APPLICATIONS** 

- Chemical handling
- Laboratory analysis
- Pharmaceuticals
- Paint and spray shops
- Printing industry •
- Electronics
- Light assembly tasks
- Light assembly of oil-coated pieces
- Glass manufacturing
- Handling of cytostatics Intricate parts handling
- •



## DESCRIPTION

- Further testing of the TouchNTuff® by a certified body on an even wider range of chemicals confirms that it resists a greater variety of industrial chemicals for longer periods than any other nitrile disposable gloves (see page 76).
- Manufactured from nitrile, TouchNTuff® offers up to four times the puncture resistance of comparable natural-latex gloves, and three times the resistance of similar neoprene gloves.
- It contains no natural rubber proteins, which means no risk of Type I allergies for the wearer. Primary skin irritation studies and Insult Patch tests have also shown no evidence of risk from irritation or allergic contact dermatitis.
- With a unique "Thin Nitrile Technology" formulation, this glove offers easy donning and strong grip in wet or dry conditions.
- The glove is highly versatile and suitable for many different uses.
- AQL 1.5 (EN374)



92-600: Fit for special purpose

Touch N Tuff® is anti-staticity tested (EN 1149-1 & 1149-3) and meets the requirements defined in EN 1149-5

