## **Assembly Instructions**






Email: sales@nobutts.com Web: www.nobutts.com Tel: 1-888-662-8887 **Shelter type: SR8301-F** 

SR8301-F-01-07092021-USA

#### **EXPLODED VIEW**



### **PARTS LIST**

ITEM NO.	PART NAME	DRG NUMBER	Size (inch)	IMAGE	QTY.
1	S1C Frame	\$1C	78.74 x 40.74		2
2	S3C Frame	S3C	78.74 x 20.3		2
3	JF1 Bracket	JF1	8.7 x 1.6		2
4	CB1 Bracket	CB1	4.3 x 4.3 x 1.6		8
5	ST15 Tie Bar	ST15	20.15 x 1.57 x 1.57		2
6	JFT	JFT	8.66 x 5.9		1
7	ST3 Roof Tie	ST3	81.1 x 1.57 x 1.57		1
8	Post P5	P5	77.15 x 1.57 x 1.57		1
9	DR Bracket	DR	4.3 x 1.6 x 2		8
10	AR1R 1m Pitch Rafter	AR1R	45 x 11.8 OA		3
11	AR1IS 1m Pitch Infill Panel Shallow	AR1IS	45.2 x 13.5		2
12	ARFS2 Apex Roof F section 2m	ARFS2	83.1 x 2 x 2		2
13	AR1POA Roof Panel outer alu	AR1POA	41.5 x 24.4		4
14	AR1CLT2 1m Apex Roof centre lower trim 2m	AR1CLT2-02	82.9 x 3.1		1
15	AR1CUT2 1m Apex Roof centre upper trim 2m	AR1CUT2	83.1 x 3.9		1
16	AR1TS 1m Apex Roof Trim strips	AR1TS	24.8 x 2.3		2
17	FT1 BRACKET	FT1	1.57 x 1.57 x 3.94		3
18	FT3 Bracket	FT3	1.57 x 3.15 x 4.17		3
19	40x40 Plastic End Cap	EC40	1.6 x 1.6		6

### **FIXINGS**

Fittings	Bolt set M10			T25	T38		BTANCM12100
	M10 x 60mm	Nut	Washer	1" Tech screw	1.5" Tech screw	Black Caps	M10/12 x 100mm Concrete Bolt
Pack A+B	33	33	66	136	40	66	11
lmage							

#### <u>Tools required:</u>



Drill/Screwdriver



17mm Wrench





Mallet




T25 Torx bit

**Step 1** Assemble **S1C** and **S3C** frames to make up the main structure using **CB1** brackets for the corners and **JF1** brackets for the straight joints.






**Step 2** Attach **ST15** Tie bars to **S3C** frames using **CB1** Brackets. Assemble the **ST15** Tie Bars with the **ST3** Tie bar and the **P5** Post, using the **CB1** Corner Brackets and the **JFT** Bracket as shown below.




#### Step 3

Attach AR1R rafters using DR brackets. Secure the AR1IS to S1 frames using tec screws. The end rafters need to be placed in position at the same time as the AR1IS.




#### Step 4

Attach the AR1CLT2 to the top of the rafters. The ARFS2 parts are to be attached to the lower part of the rafters as shown below.




Step 5
Attach the AR1POA roof panels to the top of the rafters.
Cap off the top using AR1CUT2 trim as shown.
Use the AR1TS strips to cover the gaps between the panels.

Once the shelter is in the final position and square, it can be secured to the ground using the FT3 and FT1 brackets.



**PLAN VIEW** 

OVERALL DIMENSIONS AND GROUND FIXING POSITIONS Suggested size for concrete base: 7.8" oversized on all 4 sides.



# THANK YOU FOR PURCHASING THIS PRODUCT

#### **MAINTENANCE:**

To ensure your products give you many years of use we recommend that you:

- Clean panels regularly with soapy water
- Ensure all fittings are tight (for example after a big storm)
- Touch up any exposed metal should it get scratched

#### **CONTACT DETAILS:**

Email : Sales@nobutts.com Web : www.nobutts.com

Tel: 1-888-662-8887

No Butts Bin Company, Inc. 16 Birch Lane, Madison, CT 06443

All Parts and Fixings checked by:				
Print Name:	Signature:			